

## Class tonda 330

IP 65 IK 10 20J xx9

Diffusore in policarbonato. Guarnizione in silicone.

Lampade dim. max: E27 196 mm Ø 58 mm.  
Versione doppia: lampade dim. max: E27 180 mm Ø 58 mm.

Polycarbonate diffuser. Silicone gasket.  
Lamp max. dim: E27 196 mm Ø 58 mm.  
Double version: Lamp max. dim: E27 180 mm Ø 58 mm

Diffuseur en polycarbonate. Joint en silicone.  
Lampes dim. max: E27 196 mm Ø 58 mm.  
Version double - Lampes dim. max: E27 180 mm Ø 58 mm.




= 6

Specif.	Col.	Opal.	Semitrasp.
54 LED 1950 lm 18W real lm 1256 Opal. 1701 Semitr.	○	LL581Q1□	LL582Q1□
	●	LL581Q2□	LL582Q2□
	■	LL581QG□	LL582QG□
	▲	LL581QK□	LL582QK□
36 LED 1950 lm 18W + 4 LED Em. - 180 lm real lm 1256 Opal. 1701 Semitr.	○	LL581B1□	LL582B1□
	●	LL581B2□	LL582B2□
	■	LL581BG□	LL582BG□
	▲	LL581BK□	LL582BK□

led colour
<b>N</b> = (4000K)
<b>3</b> = (3000K, lm -5%)

Lamp.	Specif.	Energy	Col.	Opal.	Semitrasp.
E27 max 1x100W CFL 1x33W	CL.II		○	LB58121	LB58221
			●	LB58122	LB58222
			■	LB5812G	LB5822G
			▲	LB5812K	LB5822K
E27 max 2x60W CFL 2x30W	CL.II		○	LB581M1	LB582M1
			●	LB581M2	LB582M2
			■	LB581MG	LB582MG
			▲	LB581MK	LB582MK
E27 max 1x20W + 2G11 1x18W Em.	CL.I		○		LB582S1
			●		LB582S2
			■		LB582SG

Disponibile a richiesta versioni a led in doppia accensione o doppia accensione + emergenza  
Available on request: led double switching and double switching + emergency  
Disponible sur demande versions led double allumage et double allumage + secur



## Nova tonda 260

IP 44 IK 06 1J xx3

Diffusore in vetro acidato. Lampade dim. max: E27 128 mm Ø 48 mm.

Acid-etched glass diffuser.  
Lamp max. dim: E27 128 mm Ø 48 mm.

Diffuseur en verre acidé.  
Lampes dim. max: E27 128 mm Ø 48 mm.



= 10

Specif.	Col.	Vetro/Glass
54 LED 1950 lm 18W real output lm 1515	○	LL802P1□
	●	LL802P2□
	■	LL802PG□
	▲	LL802PK□
72 LED 780 lm 10,2W real output lm 365	○	LL802H1□
	●	LL802H2□
	■	LL802HG□
	▲	LL802HK□
72 LED - 780 lm 10,2W + 12 LED Em. - 85 lm real output lm 365	○	LL802A1□
	●	LL802A2□
	■	LL802AG□
	▲	LL802AK□

led colour
<b>N</b> = (4000K)
<b>3</b> = (3000K, lm -5%)

Lamp.	Specif.	Energy	Col.	Vetro/Glass
E27 max 1x75W CFL 1x15W	CL.II		○	LB80221
			●	LB80222
			■	LB8022G
			▲	LB8022K

