Stile next 506L

Generality

Type of product	Post, Wall, Wall recess, Ceiling recess, Ceiling
Diffuser	Serigraphed glass
Model	Stile next
Producer	Lombardo S.r.l.
Design	design by Lombardo design department
Code	LL661D
E.A.N. code	
Pieces per package	4 pieces

N = (4000K)
3 = (3000K, lm -5%)
2 = (2700K, lm -5%)



Characteristic

Insulation class	CL.I
Type of protection	IP 66
IK	IK 06 1J xx3
Lamp type	28 LED 720 lm 6W real output lm 217 Led versions with integral ballast
Energy performance class	A A+ A++

Standards and Marks of Conformity

CE

Product description

Suitable for indoor and outdoor use.
Body made of EN-AB44100 die-cast aluminium primary alloy; highly resistant to oxidization due to the zirconium-based passivation treatment and UV stabilized polyester resin coating.
Heat tempered and serigraphed glass diffuser.
Silicone gaskets.
A4 or AISI 316L stainless steel nuts and bolts.
Patented model.
Natural white (N) or 3000K (3) LED. Integral ballast 220-240V.
No risk of photobiological damage, RG0 group (EN62471).
Possible choice of serigraphed glass in 3 different colours: black – HT grey – Corten. Double cable entry at the back.

Lombardo S.r.l.
24060 Villongo (Bergamo) ITALIA
Via Pizzigoni, 3

Tel.: 0039 035 939 411
Fax: 0039 035 939 496
Tel. Export: 0039 035 939 495
http://www.lombardo.it

Info: info@lombardo.it
Italia: commerciale.italia@lombardo.it
Export: export@lombardo.it
Ufficio Tecnico: tecnico@lombardo.it