




### Kit-04 Line Down Post H1500

DIFF. POLIGLASS

POSITION



IP 66 IK 08 5J xx7 CE

LED	W	LM	REAL LM	COL.	CODE *	* LED COLOUR
A++					LL113014□	N 4000K
	6	620	431		LL113015□	3 3000K, lm -5%
					LL113016□	2 2700K, lm -5%
					LL113017□	

Kit composto dagli attuali codici LL113001N/3/2 + LB1130001/2/3/4 + LB1100022/G/E/K + LB1130006


Kit consisting of the current codes LL113001N/3/2 + LB1130001/2/3/4 + LB1100022/G/E/K + LB1130006

Kit composé des codes actuels LL113001N/3/2 + LB1130001/2/3/4 + LB1100022/G/E/K + LB1130006

### Kit-05 Line 220 Post H500

DIFF. POLIGLASS

POSITION



IP 66 IK 08 5J xx7 CE

LED	W	LM	REAL LM	COL.	CODE *	* LED COLOUR
A++					LL113104□	N 4000K
	11	1350	910		LL113105□	3 3000K, lm -5%
					LL113106□	2 2700K, lm -5%
					LL113107□	

Kit composto dagli attuali codici LL113100N/3/2 + LB11112/G/E/K + LB1130006


Kit consisting of the current codes LL113100N/3/2 + LB11112/G/E/K + LB1130006

Kit composé des codes actuels LL113100N/3/2 + LB11112/G/E/K + LB1130006

### Kit-06 Line 220 Post H1500

DIFF. POLIGLASS

POSITION



IP 66 IK 08 5J xx7 CE

LED	W	LM	REAL LM	COL.	CODE *	* LED COLOUR
A++					LL113108□	N 4000K
	11	1350	910		LL113109□	3 3000K, lm -5%
					LL113110□	2 2700K, lm -5%
					LL113111□	

Kit composto dagli attuali codici LL113100N/3/2 + LB1100022/G/E/K + LB1130006

Kit consisting of the current codes LL113100N/3/2 + LB1100022/G/E/K + LB1130006

Kit composé des codes actuels LL113100N/3/2 + LB1100022/G/E/K + LB1130006

#### Finishing

Nero da stampaggio  
 Black  
 Noir moulé  
 Grigio High Tech  
 Grey High Tech  
 Gris High Tech  
 Grigio antracite  
 Grey anthracite  
 Gris anthracite

Corten  
 Corten  
 Corten  
 Nero verniciato  
 Black painted  
 Noir peint

**\* Led colour**  
 4000K  
 3000K, lm -5%  
 2700K, lm -5%

**Completa il codice** sostituendo al quadrato rosso la lettera o il numero corrispondente alla temperatura colore scelta.

**Complete the code** by replacing the red box with the letter or number corresponding to the selected colour temperature.

**Compléter le code** en remplaçant le carré rouge par la lettre ou le numéro correspondant à la sélection de température couleur.

**Alimentazione diretta**  
 Integral ballast  
 Alimentation intégrée  
 220-240 V

**Alimentatore escluso**  
 Ballast not included  
 Sans alimentation

