


Stile next 103

	LED	Specif.	Col.	Vetro/Glass
IP 66 IK 06 1J xx3 CE Predisposto per singolo ingresso alimentazione. LL643DN/3 alimentatore escluso. <i>Single cable entry at the back.</i> LL643DN/3 ballast not included. <i>Entrée d'alimentation simple.</i> LL643DN/3 ballast exclus.	6 LED	CL.I €		LL642C □
	14 LED	CL.I €		LL642D □
	14 LED	CL.III €		LL643D □
				led colour N = (4000K) 3 = (3000K, lm -5%)

A+ A+ A+



□ = 4




Stile next 106E

	LED	Specif.	Col.	Vetro/Glass
IP 66 IK 06 1J xx3 CE Predisposto per doppio ingresso alimentazione. LL653DN/3 alimentatore escluso. <i>Double cable entry at the back.</i> LL653DN/3 ballast not included. Possibilità alimentazione double entrée. LL653DN/3 ballast exclus.	28 LED	CL.I €		LL652D □
	28 LED	CL.III €		LL653D □
	30 LED	CL.I €		LL6523 □
	30 LED	CL.I €		LL652P □
				led colour N = (4000K) 3 = (3000K, lm -5%)

A+ A+ A+



□ = 4




Stile next 106L

	LED	Specif.	Col.	Vetro/Glass
IP 66 IK 06 1J xx3 CE Predisposto per doppio ingresso alimentazione. LL663DN/3 alimentatore escluso. <i>Double cable entry at the back.</i> LL663DN/3 ballast not included. Possibilità alimentazione double entrée. LL663DN/3 ballast exclus.	28 LED	CL.I €		LL662D □
	28 LED	CL.III €		LL663D □
	30 LED	CL.I €		LL6623 □
	30 LED	CL.I €		LL662P □
				led colour N = (4000K) 3 = (3000K, lm -5%)

A+ A+ A+




□ = 4



Stile next 103 asimmetrica

	LED	Specif.	Col.	Vetro/Glass
IP 66 IK 06 1J xx3 CE Predisposto per singolo ingresso alimentazione. Deflettore in alluminio primario pressofuso EN-AB44100. <i>Single cable entry at the back.</i> Reflector made of EN-AB44100 die-cast aluminium primary alloy. <i>Entrée d'alimentation simple.</i> Réflecteur en aluminium primaire injecté EN-AB44100	6 LED	CL.I €		LL644C □
				led colour N = (4000K) 3 = (3000K, lm -5%)

A+ A+ A+



□ = 4

