

# Stile Next

design: Lombardo design department

Accessori - Accessories - Accessoires p. 70

## Stile next zero 120T

IP 67 IK 10 20J xx9

Max 2000 Kg Max 55°C

Temperatura massima rilevata sul vetro 55°C.

Max temperature on the glass 55°C.

Température relevée sur le verre 55°C maxi.

= 4

24 LED  
725 lm 4,5W  
real output lm 260

Specif.

CL.II €

Col.


Vetro/Glass

LL677H

led colour

= (4000K)

= (3000K, lm -5%)



## Stile next zero power 120T

IP 67 IK 10 20J xx9

Max 2000 Kg Max 70°C

Temperatura massima rilevata sul vetro 70°C.

Max temperature on the glass 70°C.

Température relevée sur le verre 70°C maxi.

= 4

1 LED  
900 lm 8W  
real output lm 502

Specif.

CL.II €

Col.

Vetro/Glass

LL697H

LL697C

optic

= 10°


= 20°

= 40°

led colour

= (4000K)

= (3000K, lm -5%)



## Stile next zero 60T

IP 67 IK 10 20J xx9

Max 2000 Kg Max 60°C

Temperatura massima rilevata sul vetro 60°C.

Max temperature on the glass 60°C.

Température relevée sur le verre 60°C maxi.

= 4

1 LED  
230 lm 3W  
real output lm 38

Specif.

CL.II €

Col.


Vetro/Glass

LL104B

led colour

= (4000K)

= (3000K, lm -5%)



## Stile next zero power 60T

IP 67 IK 10 20J xx9

Max 2000 Kg Max 60°C

Temperatura massima rilevata sul vetro 60°C.

Max temperature on the glass 60°C.

Température relevée sur le verre 60°C maxi.

= 4

1 LED  
230 lm 3W  
real output lm 93

Specif.

CL.II €

Col.

Vetro/Glass

LL105B

LL105A

optic

= 13°


= 29°

= 48°

led colour

= (4000K)

= (3000K, lm -5%)



### Photometric curves - Stile next zero power 120T - LL697C

